

# Price List

## Sep 2025 (Effective from 01-09-2025)

| Products                           | Go to Page No.            |
|------------------------------------|---------------------------|
| HDTVI Camera                       | <a href="#"><u>2</u></a>  |
| DVR – Digital Video Recorder       | <a href="#"><u>3</u></a>  |
| NVR – Network Video Recorder       | <a href="#"><u>4</u></a>  |
| VDP – Video Door Phone             | <a href="#"><u>5</u></a>  |
| Access Control – Attendance System | <a href="#"><u>6</u></a>  |
| Cable – SMPS – UPS                 | <a href="#"><u>7</u></a>  |
| Monitor – Interactive Display      | <a href="#"><u>8</u></a>  |
| Wireless Alarm System              | <a href="#"><u>9</u></a>  |
| Standalone Fire Alarm              | <a href="#"><u>10</u></a> |
| Car Dash Camera                    | <a href="#"><u>11</u></a> |
| PA System                          | <a href="#"><u>12</u></a> |

**Servius Infotech Private Limited**

### Bhopal Branch

Plot No 44, , Zone-1, MP Nagar, Bhopal 462011,  
Madhya Pradesh  
Email : [parmar@servius.in](mailto:parmar@servius.in)  
Phone : 0755 - 4203580 | Mobile : 9329929100

### Indore Branch

LG – 1 & 2, Silver Sachora Castle  
RNT Marg, Indore, Madhya Pradesh  
Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)  
Phone : 0731 - 4963851 | Mobile : 9329929101

| 2 MEGA PIXEL CAMERA                                                   |        |                                                            |                |         |                                              |                           |
|-----------------------------------------------------------------------|--------|------------------------------------------------------------|----------------|---------|----------------------------------------------|---------------------------|
| MODEL NUMBER                                                          | TYPE   | FEATURE                                                    | IR DISTANCE    | LENSE   | PRICE                                        | DATA SHEET                |
| DS-2CE5AD0T-ITP/ECO                                                   | DOME   | NIL                                                        | 12 IR - 20M    | 2.8/3.6 | ₹ 640.00                                     | <a href="#">Datasheet</a> |
| DS-2CE1AD0T-ITP/ECO                                                   | BULLET | NIL                                                        | 12 IR - 20M    | 3.6     | ₹ 700.00                                     | <a href="#">Datasheet</a> |
| DS-2CE76D0T-ITPFS                                                     | DOME   | AUDIO                                                      | EXIIR - 20M    | 2.8/3.6 | ₹ 770.00                                     | <a href="#">Datasheet</a> |
| DS-2CE16D0T-ITPFS                                                     | BULLET | AUDIO                                                      | EXIR - 20M     | 3.6     | ₹ 850.00                                     | <a href="#">Datasheet</a> |
| DS-2CE76D0T-LPFS                                                      | DOME   | AUDIO - HYBRID LIGHT                                       | COLOR - 20M    | 2.8/3.6 | ₹ 1,080.00                                   | <a href="#">Datasheet</a> |
| DS-2CE16D0T-LPFS                                                      | BULLET | AUDIO - HYBRID LIGHT                                       | COLOR - 20M    | 3.6     | ₹ 1,130.00                                   | <a href="#">Datasheet</a> |
| DS-2CE70D0T-PTLTS                                                     | DOME   | TWO WAY AUDIO - HYBRID                                     | PT COLOR - 20M | 2.8/3.6 | ₹ 1,570.00                                   | <a href="#">Datasheet</a> |
| DS-2CE16D0T-LPTS                                                      | BULLET | TWO WAY AUDIO - HYBRID                                     | COLOR - 20M    | 3.6     | ₹ 1,470.00                                   | <a href="#">Datasheet</a> |
| DS-2CE70DF0T-PFS                                                      | DOME   | COLOR - AUDIO                                              | COLOR - 20M    | 2.8/3.6 | ₹ 1,580.00                                   | <a href="#">Datasheet</a> |
| DS-2CE10DF0T-PFS                                                      | BULLET | COLOR - AUDIO                                              | COLOR - 20M    | 2.6     | ₹ 1,640.00                                   | <a href="#">Datasheet</a> |
| DS-2CE18D0T-LFS                                                       | BULLET | LAMP - AUDIO                                               | LAMP - 20M     | 3.6     | ₹ 1,700.00                                   | <a href="#">Datasheet</a> |
| 2K/5MP/3K MEGA PIXEL CAMERA                                           |        |                                                            |                |         |                                              |                           |
| MODEL NUMBER                                                          | TYPE   | FEATURE                                                    | IR DISTANCE    | LENSE   | PRICE                                        | DATA SHEET                |
| DS-2CE76H0T-ITPFS                                                     | DOME   | AUDIO, DWDR                                                | EXIR - 20M     | 2.8/3.6 | ₹ 1,200.00                                   | <a href="#">Datasheet</a> |
| DS-2CE16H0T-ITPFS                                                     | BULLET | AUDIO, DWDR                                                | EXIR - 20M     | 3.6     | ₹ 1,260.00                                   | <a href="#">Datasheet</a> |
| DS-2CE76G0T-LPFS                                                      | DOME   | AUDIO - HYBRID LIGHT                                       | EXIR - 20M     | 2.8/3.6 | ₹ 1,250.00                                   | <a href="#">Datasheet</a> |
| DS-2CE16G0T-LPFS                                                      | BULLET | AUDIO - HYBRID LIGHT                                       | EXIR - 20M     | 3.6     | ₹ 1,320.00                                   | <a href="#">Datasheet</a> |
| DS-2CE76K0T-LPFS                                                      | DOME   | AUDIO - HYBRID LIGHT                                       | COLOR - 20M    | 2.8/3.6 | ₹ 1,450.00                                   | <a href="#">Datasheet</a> |
| DS-2CE16K0T-LPFS                                                      | BULLET | AUDIO - HYBRID LIGHT                                       | COLOR - 20M    | 3.6     | ₹ 1,530.00                                   | <a href="#">Datasheet</a> |
| DS-2CE78K0T-LTS                                                       | DOME   | TWO WAY AUDIO - HYBRID                                     | COLOR - 20M    | 2.8/3.6 | ₹ 1,750.00                                   | <a href="#">Datasheet</a> |
| DS-2CE16K0T-LPTS                                                      | BULLET | TWO WAY AUDIO - HYBRID                                     | COLOR - 20M    | 3.6     | ₹ 1,750.00                                   | <a href="#">Datasheet</a> |
| DS-2CE70KF0T-PFS                                                      | DOME   | COLOR - AUDIO, 3K                                          | COLOR - 20M    | 3.6     | ₹ 2,100.00                                   | <a href="#">Datasheet</a> |
| DS-2CE10KF0T-PFS                                                      | BULLET | COLOR - AUDIO, 3K                                          | COLOR - 20M    | 3.6     | ₹ 2,160.00                                   | <a href="#">Datasheet</a> |
| Authorized Distributor -                                              |        | Bhopal Branch                                              |                |         | Indore Branch                                |                           |
| Servius Infotech Pvt. Ltd.                                            |        | Plot No 44, Zone-1 MP Nagar, Bhopal 462011, Madhya Pradesh |                |         | LG - 1 & 2, Silver Sachora Castle            |                           |
| CIN : U72200MP2015PTC034176                                           |        | Email : parmar@servius.in                                  |                |         | RNT Marg, Indore, Madhya Pradesh             |                           |
| Website : <a href="https://www.servius.in">https://www.servius.in</a> |        | Phone : 0755 - 4203580   Mobile : 9329929100               |                |         | Email : setu.dangi@servius.in                |                           |
|                                                                       |        |                                                            |                |         | Phone : 0731 - 4963851   Mobile : 9329929101 |                           |

| ECO SERIES DVR                                                        |       |                                                                  |     |                                                                          |                           |
|-----------------------------------------------------------------------|-------|------------------------------------------------------------------|-----|--------------------------------------------------------------------------|---------------------------|
| MODEL NUMBER                                                          | CH    | FEATURE                                                          | IP  | PRICE                                                                    | DATA SHEET                |
| DS-7104HGHI-M1/T                                                      | 04-Ch | ECO 720P\1080P Lite 1HDD H.265Pro+ DVR                           | NIL | ₹ 2,080.00                                                               | <a href="#">Datasheet</a> |
| DS-7108HGHI-M1/T                                                      | 08-Ch | ECO 720P\1080P Lite 1HDD H.265Pro+ DVR                           | NIL | ₹ 3,030.00                                                               | <a href="#">Datasheet</a> |
| DS-7116HGHI-M1/T                                                      | 16-Ch | ECO 720P\1080P Lite 1HDD H.265Pro+ DVR                           | NIL | ₹ 5,130.00                                                               | <a href="#">Datasheet</a> |
| DS-7232HGHI-M2                                                        | 32-Ch | ECO 720P\1080P Lite 1HDD H.265Pro+ DVR                           | 2   | ₹ 17,400.00                                                              | <a href="#">Datasheet</a> |
| 3K\5 MP Lite DVR                                                      |       |                                                                  |     |                                                                          |                           |
| MODEL NUMBER                                                          | CH    | FEATURE                                                          | IP  | PRICE                                                                    | DATA SHEET                |
| iDS-7104HQHI-M1/S                                                     | 04-Ch | 3K\5MP Lite 1HDD H.265Pro+ AcuSense                              | 2   | ₹ 3,300.00                                                               | <a href="#">Datasheet</a> |
| iDS-7204HQHI-M1/XT                                                    | 04-Ch | 3K\5MP Lite 1HDD H.265Pro+ AcuSense, <b>Powe</b>                 | 2   | ₹ 3,880.00                                                               | <a href="#">Datasheet</a> |
| iDS-7108HQHI-M1/S                                                     | 08-Ch | 3K\5MP Lite 1HDD H.265Pro+ AcuSense                              | 4   | ₹ 4,740.00                                                               | <a href="#">Datasheet</a> |
| iDS-7208HQHI-M1/XT                                                    | 08-Ch | 3K\5MP Lite 1HDD H.265Pro+ AcuSense, <b>Powe</b>                 | 4   | ₹ 5,650.00                                                               | <a href="#">Datasheet</a> |
| iDS-7208HQHI-M2/XT                                                    | 08-Ch | 3K\5MP Lite 2HDD H.265Pro+ AcuSense, <b>Powe</b>                 | 4   | ₹ 8,170.00                                                               | <a href="#">Datasheet</a> |
| iDS-7116HQHI-M1/S                                                     | 16-Ch | 3K\5MP Lite 1HDD H.265Pro+ AcuSense                              | 8   | ₹ 8,190.00                                                               | <a href="#">Datasheet</a> |
| iDS-7216HQHI-M1/XT                                                    | 16-Ch | 3K\5MP Lite 1HDD H.265Pro+ AcuSense, <b>Powe</b>                 | 8   | ₹ 9,800.00                                                               | <a href="#">Datasheet</a> |
| iDS-7216HQHI-M2/XT                                                    | 16-Ch | 3K\5MP Lite 2HDD H.265Pro+ AcuSense, <b>Powe</b>                 | 8   | ₹ 13,000.00                                                              | <a href="#">Datasheet</a> |
| iDS-7232HQHI-M2/XT                                                    | 32-Ch | 3K\5MP Lite 2HDD H.265Pro+ AcuSense, <b>Powe</b>                 | 8   | ₹ 21,400.00                                                              | <a href="#">Datasheet</a> |
| 5MP\8MP MP DVR                                                        |       |                                                                  |     |                                                                          |                           |
| MODEL NUMBER                                                          | CH    | FEATURE                                                          | IP  | PRICE                                                                    | DATA SHEET                |
| iDS-7204HUHI-M1/X                                                     | 04-Ch | 5MP\8MP 1HDD H.265Pro+ AcuSense, <b>PowerX</b>                   | 4   | ₹ 4,890.00                                                               | <a href="#">Datasheet</a> |
| iDS-7208HUHI-M1/X                                                     | 08-Ch | 5MP\8MP 1HDD H.265Pro+ AcuSense, <b>PowerX</b>                   | 8   | ₹ 7,890.00                                                               | <a href="#">Datasheet</a> |
| iDS-7216HUHI-M2/X                                                     | 16-Ch | 5MP\8MP 2HDD H.265Pro+ AcuSense, <b>PowerX</b>                   | 16  | ₹ 14,100.00                                                              | <a href="#">Datasheet</a> |
| Authorized Distributor -                                              |       | Bhopal Branch                                                    |     | Indore Branch                                                            |                           |
| <b>Servius Infotech Pvt. Ltd.</b>                                     |       | Plot No 44, Zone-1,                                              |     | LG - 1 & 2, Silver Sachora Castle                                        |                           |
| CIN : U72200MP2015PTC034176                                           |       | MP Nagar, Bhopal 462011, Madhya Pradesh                          |     | RNT Marg, Indore, Madhya Pradesh                                         |                           |
| Website : <a href="https://www.servius.in">https://www.servius.in</a> |       | Email : <a href="mailto:parmar@servius.in">parmar@servius.in</a> |     | Email : <a href="mailto:setu.dangi@servius.in">setu.dangi@servius.in</a> |                           |
|                                                                       |       | Phone : 0755 - 4203580   Mobile : 9329929100                     |     | Phone : 0731 - 4963851   Mobile : 9329929101                             |                           |

| Q - SERIES     |       |                                             |            |                           |
|----------------|-------|---------------------------------------------|------------|---------------------------|
| MODEL NUMBER   | CH    | FEATURE                                     | PRICE      | DATA SHEET                |
| DS-7104NI-Q1/M | 04-Ch | 1 HDD H.265+ NVR, Recomonded for 2MP Camera | ₹ 3,150.00 | <a href="#">Datasheet</a> |
| DS-7108NI-Q1/M | 08-Ch | 1 HDD H.265+ NVR, Recomonded for 2MP Camera | ₹ 3,750.00 | <a href="#">Datasheet</a> |
| DS-7116NI-Q1/M | 16-Ch | 1 HDD H.265+ NVR, Recomonded for 2MP Camera | ₹ 5,300.00 | <a href="#">Datasheet</a> |
| DS-7604NI-Q1   | 04-Ch | 1 HDD H.265+ NVR, Recomonded for 4MP Camera | ₹ 4,600.00 | <a href="#">Datasheet</a> |
| DS-7608NI-Q1   | 08-Ch | 1 HDD H.265+ NVR, Recomonded for 4MP Camera | ₹ 5,100.00 | <a href="#">Datasheet</a> |
| DS-7608NI-Q2   | 08-Ch | 2 HDD H.265+ NVR, Recomonded for 4MP Camera | ₹ 6,200.00 | <a href="#">Datasheet</a> |
| DS-7616NI-Q1   | 16-Ch | 1 HDD H.265+ NVR, Recomonded for 4MP Camera | ₹ 5,900.00 | <a href="#">Datasheet</a> |
| DS-7616NI-Q2   | 16-Ch | 2 HDD H.265+ NVR, Recomonded for 4MP Camera | ₹ 7,350.00 | <a href="#">Datasheet</a> |

| K - SERIES    |       |                                             |             |                           |
|---------------|-------|---------------------------------------------|-------------|---------------------------|
| MODEL NUMBER  | CH    | FEATURE                                     | PRICE       | DATA SHEET                |
| DS-7604NXI-K1 | 04-Ch | 1 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 6,050.00  | <a href="#">Datasheet</a> |
| DS-7608NXI-K1 | 08-Ch | 1 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 6,650.00  | <a href="#">Datasheet</a> |
| DS-7608NXI-K2 | 08-Ch | 2 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 8,350.00  | <a href="#">Datasheet</a> |
| DS-7616NXI-K1 | 16-Ch | 1 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 7,950.00  | <a href="#">Datasheet</a> |
| DS-7616NXI-K2 | 16-Ch | 2 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 9,400.00  | <a href="#">Datasheet</a> |
| DS-7716NXI-K4 | 16-Ch | 4 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 18,700.00 | <a href="#">Datasheet</a> |
| DS-7632NXI-K2 | 32-Ch | 2 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 12,075.00 | <a href="#">Datasheet</a> |
| DS-7732NXI-K4 | 32-Ch | 4 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 22,600.00 | <a href="#">Datasheet</a> |
| DS-7764NI-M4  | 64-Ch | 4 HDD H.265+ NVR, Recomonded for 6MP Camera | ₹ 31,000.00 | <a href="#">Datasheet</a> |

Authorized Distributor -

**Servius Infotech Pvt. Ltd.**

CIN : U72200MP2015PTC034176

Website : <https://www.servius.in>**Bhopal Branch**Plot No 44, Zone-1, MP Nagar, Bhopal 462011,  
Madhya PradeshEmail : [parmar@servius.in](mailto:parmar@servius.in)

Phone : 0755 - 4203580 | Mobile : 9329929100

**Indore Branch**LG - 1 & 2, Silver Sachora Castle  
RNT Marg, Indore, Madhya PradeshEmail : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)

Phone : 0731 - 4963851 | Mobile : 9329929101

| VIDEO DOOR PHONE  |                                                                                     |                                                                                                                                                                                                                                                                                                                      |             |                           |
|-------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|---------------------------|
| MODEL NUMBER      |                                                                                     | FEATURE                                                                                                                                                                                                                                                                                                              | PRICE       | DATA SHEET                |
| DS-KIS205T        |    | 4-wire analog video intercom bundle for villa or house<br>One call button for easier calls<br>Including DS-KB2411T-IM and DS-KH2220, 5-meter 4-wire cable, and other accessories                                                                                                                                     | ₹ 4,400.00  | <a href="#">Datasheet</a> |
| DS-KIS212         |    | 4-Wire HD Video Intercom Kit<br>HD TVI video quality, Plug & play, One-press to call<br>One-press to unlock the door<br>Support Max 2 door stations and 3 indoor stations in one system                                                                                                                              | ₹ 4,200.00  | <a href="#">Datasheet</a> |
| DS-KH2220-S       |    | 4-wire analog indoor station<br>7-inch TFT screen with 800 × 480 resolution<br>Physical buttons design for easier operation<br>Supports three indoor stations cascading in the intercom system<br>Supports remote unlocking, monitoring door station and external analog camera<br>Supports captured picture storage | ₹ 2,800.00  | <a href="#">Datasheet</a> |
| DS-KIS603-P(C)    |    | 7-inch colorful touch screen<br>Access control functions<br>Storage in the TF card<br>Remote unlocking via the client software or the mobile client<br>Supports wireless network                                                                                                                                     | ₹ 11,450.00 | <a href="#">Datasheet</a> |
| DS-KIS602         |    | 7-inch colorful touch screen<br>Storage in the TF card<br>Remote unlocking via the client software or the mobile client<br>Views live videos of door stations and linked cameras<br>Supports wireless network<br>Access control function<br>Fisheye camera with IR supplement light                                  | ₹ 14,500.00 | <a href="#">Datasheet</a> |
| DS-KH6320-WTE1    |   | 7-inch colorful touch screen<br>Storage in the TF card<br>Remote unlocking via the client software or the mobile client<br>Views live videos of door stations and linked cameras<br>Supports wireless network                                                                                                        | ₹ 5,300.00  | <a href="#">Datasheet</a> |
| DS-KH6350-WTE1    |  | 7-inch colorful touch screen<br>Storage in the TF card<br>Remote unlocking via the client software or the mobile client<br>Views live videos of door stations and linked cameras<br>Supports wireless network                                                                                                        | ₹ 5,400.00  | <a href="#">Datasheet</a> |
| DS-KV6113-WPE1(C) |  | 2 MP camera with IR supplement<br>One-touch button calling design for easier calls<br>Built-in card reader module<br>IP65 protection level                                                                                                                                                                           | ₹ 5,500.00  | <a href="#">Datasheet</a> |
| DS-KD8003-IME1(B) |  | 2MP HD Colorful Camera, <b>Fish eye</b> , IR Supplement<br>1 Call physical Button, 2 lock relays, 4-ch alarm input<br>IP65 Protection Level                                                                                                                                                                          | ₹ 8,500.00  | <a href="#">Datasheet</a> |
| DS-KV8413-WME1(C) |  | 2 MP HD camera, Low illumination<br>Access control functions<br>2.4 GHz Wi-Fi<br>Protection level: IK08                                                                                                                                                                                                              | ₹ 8,700.00  | <a href="#">Datasheet</a> |

Authorized Distributor -

**Servius Infotech Pvt. Ltd.**

CIN : U72200MP2015PTC034176

Website : <https://www.servius.in>**Bhopal Branch**

Plot No 44, Zone-1, MP Nagar, Bhopal 462011, Madhya Pradesh

Email : [parmar@servius.in](mailto:parmar@servius.in)

Phone : 0755 - 4203580 | Mobile : 9329929100

**Indore Branch**

LG - 1 &amp; 2, Silver Sachora Castle

RNT Marg, Indore, Madhya Pradesh

Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)

Phone : 0731 - 4963851 | Mobile : 9329929101

## ATTENDANCE SYSTEM



Model Selection : (E) - EM Card | (M) - Mifare Card | (F) - Fingerprint | (W) - WiFi | (B) - Battery

| MODEL NUMBER    |                                                                                     | FEATURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | PRICE      | DATA SHEET                |
|-----------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------|
| DS-K1A8503EF    |    | * 2.4-inch LCD screen to display time, date, week, and attendance information<br>* TCP/IP communication                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | ₹ 2,800.00 | <a href="#">Datasheet</a> |
| DS-K1A8503EF-B  |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 3,200.00 | <a href="#">Datasheet</a> |
| DS-K1T320EWX    |    | * 2.4-inch LCD screen, 2 MP lens<br>* Multiple authentication methods, including face, fingerprint, card, and PIN, etc<br>* Supports EM card, Mifare Card<br>* Max. 500 faces, 1,000 cards, 1,000 fingerprints and 100,000 events<br>* Face recognition duration < 0.2 s/User<br>* Supports ISAPI and ISUP 5.0 protocols<br>* Configuration via the web client                                                                                                                                                                                                                                                       | ₹ 3,700.00 | <a href="#">Datasheet</a> |
| DS-K1T320EFWX   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 4,250.00 | <a href="#">Datasheet</a> |
| DS-K1T320EFWX-B |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 5,300.00 | <a href="#">Datasheet</a> |
| DS-K1A340WX     |    | * Local time attendance; Remote time attendance via web browser<br>* 4.3-inch touch screen and 2 MP camera<br>* Face anti-spoofing; Face recognition distance: 0.3m to 1.5m<br>* Face recognition duration < 0.2 s/User; face recognition accuracy rate ≥ 99%<br>* Deep learning algorithm, Multiple authentication modes<br>* 1500 face capacity, 3000 fingerprint capacity, and 300,000 attendance records<br>* Export registered face pictures and events from device via USB interface<br>* Manage, search and set device data after logging in the device locally<br>* Light supplement in the dark environment | ₹ 5,400.00 | <a href="#">Datasheet</a> |
| DS-K1A340FWX    |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 6,300.00 | <a href="#">Datasheet</a> |
| DS-K1T343MWX    |   | Max.1500 faces capacity, Max.3000 fingerprints capacity, and Max.3000 cards<br>Face Recognition Terminal, 4.3-inch LCD touch screen<br>2 Mega pixel wide-angle lens,Built-in Mifare card reading module<br>Two-way audio with client software<br>indoor station, and main station; Supports TCP/IP, Wi-Fi<br>Supports ISAPI, ISUP5.0, Configuration via the web client<br>Face Recognition Distance: 0.3 m to 1.5 m<br>Duration < 0.2 s/User, Accuracy rate ≥ 99%, Supports mask recognition                                                                                                                         | ₹ 6,200.00 | <a href="#">Datasheet</a> |
| DS-K1T343EWX    |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 6,200.00 | <a href="#">Datasheet</a> |
| DS-K1T343EFWX   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 7,100.00 | <a href="#">Datasheet</a> |
| DS-K1T343MFWX   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 7,100.00 | <a href="#">Datasheet</a> |
| DS-K1T342EFWX   |  | * Max.1500 faces capacity, Max.3000 fingerprints capacity, and Max.3000 cards<br>* Face Recognition Terminal, 4.3-inch LCD touch screen,<br>* 2 Mega pixel wide-angle lens,Built-in Mifare card reading module<br>* Two-way audio with client software<br>* indoor station, and main station; Supports TCP/IP, Wi-Fi, Supports ISAPI, ISUP5.0<br>* Configuration via the web client, Face Recognition Distance: 0.3 m to 1.5 m<br>* Duration < 0.2 s/User, Accuracy rate ≥ 99%, Supports mask recognition                                                                                                            | ₹ 9,900.00 | <a href="#">Datasheet</a> |
| DS-K1T342MFWX   |                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | ₹ 9,900.00 | <a href="#">Datasheet</a> |

Authorized Distributor -

**Servius Infotech Pvt. Ltd.**  
 CIN : U72200MP2015PTC034176  
 Website : <https://www.servius.in>

**Bhopal Branch**  
 Plot No 44, Zone-1 MP Nagar, Bhopal 462011,  
 Madhya Pradesh  
 Email : [parmar@servius.in](mailto:parmar@servius.in)  
 Phone : 0755 - 4203580 | Mobile : 9329929100

**Indore Branch**  
 LG - 1 & 2, Silver Sachora Castle  
 RNT Marg, Indore, Madhya Pradesh  
 Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)  
 Phone : 0731 - 4963851 | Mobile : 9329929101

| SMPS & CABLES     |                                                                                     |                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|-------------------|-------------------------------------------------------------------------------------|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------|----------------------------|----------|-------------------------|------------|------------------------|------------|----------|----------------|--------|-----------|----------------|----------|----------------|-----------|--------------|-------|---------------|-------------|---------------------------|---------|------------------------|--|----------|-----------------------|--|-------|---------------|--|------------|---------------------------|
| MODEL NUMBER      |                                                                                     | TYPE                       | FEATURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | PRICE      | DATA SHEET                |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-2FA1205-DW-IN  |    | 5 AMP SMPS                 | BIS Approved<br>Highly Integrated SMPS Switcher I.C Design<br>Surge Protection, Over Temperature Protection<br>Over Current, Over Voltage & Over Load Protection<br>High-efficiency, low energy Consumption                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | ₹ 430.00   | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-2FA120A-DW-IN  |                                                                                     | 10 AMP SMPS                | Low Ripple Voltage (mV P-P): <5%<br>Works under low voltages and protects high voltage where linear fails<br>Wall Mountable/ Desktop Type with wall hanging hook.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | ₹ 590.00   | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-2FA120K-DW-IN  |                                                                                     | 20 AMP SMPS                | Inbuilt cooling fan for better heat dissipation.<br>Covered Input AC & Output DC terminals for safety purpose.<br>Compact size, lightweight & shock proof.<br>Screw type block terminals for easy installation.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | ₹ 960.00   | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-UPS600(IND)    |    | 600VA Offline UPS          | 1pc 12V/7AH internal batteries<br>Transfer time: DC to AC ≤10 ms; AC to DC ≤10 ms<br>Rechargeable typical recharge time: 10 to 16 hours                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | ₹ 2,000.00 | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-UPS600(IND)    |                                                                                     | 1KVA Offline UPS           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | ₹ 2,000.00 | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-3WR3X-1        |    | Wi-Fi USB Adapter          | Support Wi-Fi 6<br>Drive-free installation, plug and play<br>Compatible and adaptable with Hikvision DVR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | ₹ 360.00   | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-1LH1SCA3C-090B |    | 90 Meter Roll RG59         | RG59 coaxial cable with power cable<br>Conductor material of Coaxial cable is Bare copper<br>Braiding material of Coaxial cable is Copper clad aluminum magnesium<br>Conductor material of power cable is Bare copper<br>Excellent anti-interference performance<br>Excellent anti-aging performance                                                                                                                                                                                                                                                                                                                                                                                                       | ₹ 1,780.00 | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-1LH1SCAM593C   |                                                                                     | 180 Meter Roll RG59        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | ₹ 3,500.00 | <a href="#">Datasheet</a> |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-1LN6U-W/CCA    |  | 305 Meter Cat 6 CCA        | <table><tr><td rowspan="2">Conductor</td><td>Material</td><td colspan="2">CCA (Copper content: 27%)</td></tr><tr><td>Nom.O.D.(mm)</td><td>0.585</td><td>up +0.01<br/>down -0.01</td></tr><tr><td rowspan="2">Insulation</td><td>Material</td><td colspan="2">Solid HDPE</td></tr><tr><td>Diameter</td><td colspan="2">1.05±0.05mm</td></tr><tr><td rowspan="4">Sheath</td><td>Thickness</td><td colspan="2">0.50±0.05 mm</td></tr><tr><td>External O.D.</td><td colspan="2">6.0±0.30 mm</td></tr><tr><td>Surface</td><td colspan="2">Clean, Frap, Satiation</td></tr><tr><td>Material</td><td colspan="2">FR-PVC(Complies RoHS)</td></tr><tr><td>Color</td><td colspan="2">White RAL9003</td></tr></table> | Conductor  | Material                  | CCA (Copper content: 27%)  |          | Nom.O.D.(mm)            | 0.585      | up +0.01<br>down -0.01 | Insulation | Material | Solid HDPE     |        | Diameter  | 1.05±0.05mm    |          | Sheath         | Thickness | 0.50±0.05 mm |       | External O.D. | 6.0±0.30 mm |                           | Surface | Clean, Frap, Satiation |  | Material | FR-PVC(Complies RoHS) |  | Color | White RAL9003 |  | ₹ 4,050.00 | <a href="#">Datasheet</a> |
| Conductor         | Material                                                                            | CCA (Copper content: 27%)  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Nom.O.D.(mm)                                                                        | 0.585                      | up +0.01<br>down -0.01                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| Insulation        | Material                                                                            | Solid HDPE                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Diameter                                                                            | 1.05±0.05mm                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| Sheath            | Thickness                                                                           | 0.50±0.05 mm               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | External O.D.                                                                       | 6.0±0.30 mm                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Surface                                                                             | Clean, Frap, Satiation     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Material                                                                            | FR-PVC(Complies RoHS)      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| Color             | White RAL9003                                                                       |                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-1LN6UZC0       |  | 305 Meter Cat 6 Copper     | <table><tr><td rowspan="2">Conductor</td><td>Material</td><td>Solid-Bare Copper (99.95%)</td></tr><tr><td>Diameter</td><td>0.50 ± 0.01 mm</td></tr><tr><td rowspan="2">Insulation</td><td>Material</td><td>HDPE</td></tr><tr><td>Diameter</td><td>0.88 ± 0.05 mm</td></tr><tr><td rowspan="4">Sheath</td><td>Thickness</td><td>0.50 ± 0.05 mm</td></tr><tr><td>Diameter</td><td>5.30 ± 0.50 mm</td></tr><tr><td>Material</td><td>PVC</td></tr><tr><td>Color</td><td>Grey、Orange</td></tr></table>                                                                                                                                                                                                          | Conductor  | Material                  | Solid-Bare Copper (99.95%) | Diameter | 0.50 ± 0.01 mm          | Insulation | Material               | HDPE       | Diameter | 0.88 ± 0.05 mm | Sheath | Thickness | 0.50 ± 0.05 mm | Diameter | 5.30 ± 0.50 mm | Material  | PVC          | Color | Grey、Orange   | ₹ 7,000.00  | <a href="#">Datasheet</a> |         |                        |  |          |                       |  |       |               |  |            |                           |
| Conductor         | Material                                                                            | Solid-Bare Copper (99.95%) |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Diameter                                                                            | 0.50 ± 0.01 mm             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| Insulation        | Material                                                                            | HDPE                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Diameter                                                                            | 0.88 ± 0.05 mm             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| Sheath            | Thickness                                                                           | 0.50 ± 0.05 mm             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Diameter                                                                            | 5.30 ± 0.50 mm             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Material                                                                            | PVC                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Color                                                                               | Grey、Orange                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| DS-1LN6U-G        |  | 305 Meter Cat 6 Copper     | <table><tr><td rowspan="2">Conductor</td><td>Material</td><td>Solid-Bare Copper (99.95%)</td></tr><tr><td>Diameter</td><td>0.55 ± 0.005 mm, 23 AWG</td></tr><tr><td rowspan="2">Insulation</td><td>Material</td><td>HDPE</td></tr><tr><td>Diameter</td><td>0.98 ± 0.05 mm</td></tr><tr><td rowspan="4">Sheath</td><td>Thickness</td><td>0.50 ± 0.10 mm</td></tr><tr><td>Diameter</td><td>6.00 ± 0.30 mm</td></tr><tr><td>Material</td><td>PVC</td></tr><tr><td>Color</td><td>Grey</td></tr></table>                                                                                                                                                                                                        | Conductor  | Material                  | Solid-Bare Copper (99.95%) | Diameter | 0.55 ± 0.005 mm, 23 AWG | Insulation | Material               | HDPE       | Diameter | 0.98 ± 0.05 mm | Sheath | Thickness | 0.50 ± 0.10 mm | Diameter | 6.00 ± 0.30 mm | Material  | PVC          | Color | Grey          | ₹ 8,690.00  | <a href="#">Datasheet</a> |         |                        |  |          |                       |  |       |               |  |            |                           |
| Conductor         | Material                                                                            | Solid-Bare Copper (99.95%) |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Diameter                                                                            | 0.55 ± 0.005 mm, 23 AWG    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| Insulation        | Material                                                                            | HDPE                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Diameter                                                                            | 0.98 ± 0.05 mm             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
| Sheath            | Thickness                                                                           | 0.50 ± 0.10 mm             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Diameter                                                                            | 6.00 ± 0.30 mm             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Material                                                                            | PVC                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |
|                   | Color                                                                               | Grey                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |            |                           |                            |          |                         |            |                        |            |          |                |        |           |                |          |                |           |              |       |               |             |                           |         |                        |  |          |                       |  |       |               |  |            |                           |

Authorized Distributor -

**Servius Infotech Pvt. Ltd.**  
CIN : U72200MP2015PTC034176  
Website : <https://www.servius.in>

**Bhopal Branch**  
Plot No 44, Zone-1, MP Nagar, Bhopal 462011, Madhya Pradesh  
Email : [parmar@servius.in](mailto:parmar@servius.in)  
Phone : 0755 - 4203580 | Mobile : 9329929100

**Indore Branch**  
LG - 1 & 2, Silver Sachora Castle  
RNT Marg, Indore, Madhya Pradesh  
Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)  
Phone : 0731 - 4963851 | Mobile : 9329929101



| SMPS & CABLES |                                                                                   |                                            |                                                                                                                                                                                                                                                                                                              |               |                           |
|---------------|-----------------------------------------------------------------------------------|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------------------|
| MODEL NUMBER  |                                                                                   | TYPE                                       | FEATURE                                                                                                                                                                                                                                                                                                      | PRICE         | DATA SHEET                |
| DS-D5022QE-D  |  | 22 Inch<br>CCTV Monitor                    | LED backlit technology with full HD 1920 x 1080<br>Wide view angle: 178°(H)/178°(V)<br>Multiply inputs: HDMI, VGA<br>3D comb filter, 3D De-interlace<br>3D noise reduction<br>VESA stand bracket<br>High reliability and stability, 24/7 operation<br>Green energy: Enter standby mode while no signal input | ₹ 4,100.00    | <a href="#">Datasheet</a> |
| DS-D5032QE    |  | 32 Inch<br>CCTV Monitor                    | 8 bit LVDS FHD (1920 × 1080) display.<br>178° ultra-wide view screen.<br>Auto signal input Detection<br>Dual interface of HDMI and VGA.                                                                                                                                                                      | ₹ 12,200.00   | <a href="#">Datasheet</a> |
| DS-D5043QE    |                                                                                   | 43 Inch<br>CCTV Monitor                    | Support VESA wall mount.<br>Built-in speaker<br>High reliability and stability, 24/7 operation                                                                                                                                                                                                               | ₹ 18,800.00   | <a href="#">Datasheet</a> |
| DS-D5B65RB/EL |  | 65-inch 4K<br>Interactive Display<br>8/128 | UHD 4K display with resolution of 3840 × 2160.<br>Anti-glare and anti-blocking design to ensure smooth interaction.<br>Dual systems of Android and Windows (optional) saving cost and easy to use, video conference software are recommended to run under Windows system.                                    | ₹ 80,900.00   | <a href="#">Datasheet</a> |
| DS-D5B75RB/EL |                                                                                   | 75-inch 4K<br>Interactive Display<br>8/128 | Quick response, at most 40-point touch controls and smooth writing experience.                                                                                                                                                                                                                               | ₹ 1,01,000.00 | <a href="#">Datasheet</a> |
| DS-D5B86RB/EL |                                                                                   | 86-inch 4K<br>Interactive Display<br>8/128 | Multi-button design in front, convenient for classroom use.<br>Compatible with OPS/OPS-C devices, realizing smooth switch between built-in systems.                                                                                                                                                          | ₹ 1,36,400.00 | <a href="#">Datasheet</a> |

Authorized Distributor -

Servius Infotech Pvt. Ltd.  
CIN : U72200MP2015PTC034176  
Website : <https://www.servius.in>

Bhopal Branch

Plot No 44, Zone-1, MP Nagar, Bhopal 462011, Madhya Pradesh  
Email : [parmar@servius.in](mailto:parmar@servius.in)  
Phone : 0755 - 4203580 | Mobile : 9329929100

Indore Branch

LG - 1 & 2, Silver Sachora Castle  
RNT Marg, Indore, Madhya Pradesh  
Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)  
Phone : 0731 - 4963851 | Mobile : 9329929101



| Wireless Alarm System |                                                                                     |                                                     |             |                           |
|-----------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------|-------------|---------------------------|
| MODEL NUMBER          | PICTURE                                                                             | FEATURE                                             | PRICE       | DATA SHEET                |
| DS-PWA64-Kit-WB       |    | Wireless 64 Zone Control Panel (WiFi, 2G, Ethernet) | ₹ 10,900.00 | <a href="#">Datasheet</a> |
| DS-PWA96-Kit-WB       |    | Wireless 96 Zone Control Panel (WiFi, 4G, Ethernet) | ₹ 14,580.00 | <a href="#">Datasheet</a> |
| DS-PDMC-EG2-WB        |    | Wireless Magnetic Contact                           | ₹ 1,400.00  | <a href="#">Datasheet</a> |
| DS-PDP15P-EG2-WB      |    | Wireless PIR Detector                               | ₹ 2,050.00  | <a href="#">Datasheet</a> |
| DS-PDSMK-S-WB         |    | Wireless Photoelectric Smoke Detector               | ₹ 3,140.00  | <a href="#">Datasheet</a> |
| DS-PDTPH-E-WB         |    | Wireless Temperature Detector                       | ₹ 2,500.00  | <a href="#">Datasheet</a> |
| DS-PDWL-E-WB          |   | Wireless Water Leak Detector                        | ₹ 1,850.00  | <a href="#">Datasheet</a> |
| DS-PR1-WB             |  | Wireless Repeater                                   | ₹ 4,170.00  | <a href="#">Datasheet</a> |
| DS-PDEB1-EG2-WB       |  | Wireless Emergency Button                           | ₹ 1,090.00  | <a href="#">Datasheet</a> |
| DS-PS1-I-WB           |  | Wireless Internal Sounder                           | ₹ 2,500.00  | <a href="#">Datasheet</a> |
| DS-PS1-E-WB           |  | Wireless External Sounder                           | ₹ 4,000.00  | <a href="#">Datasheet</a> |
| DS-PM1-O1H-WB         |  | Wireless Wall Switch                                | ₹ 1,740.00  | <a href="#">Datasheet</a> |
| DS-PDBG8-EG2-WB       |  | Wireless Vibration Sensor                           | ₹ 2,060.00  | <a href="#">Datasheet</a> |

Authorized Distributor -

**Servius Infotech Pvt. Ltd.**

CIN : U72200MP2015PTC034176

Website : <https://www.servius.in>**Bhopal Branch**

Plot No 44, Zone-1, MP Nagar, Bhopal 462011,

Madhya Pradesh

Email : [parmar@servius.in](mailto:parmar@servius.in)

Phone : 0755 - 4203580 | Mobile : 9329929100

**Indore Branch**

LG - 1 &amp; 2, Silver Sachora Castle

RNT Marg, Indore, Madhya Pradesh

Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)

Phone : 0731 - 4963851 | Mobile : 9329929101

| STANDALONE FIRE ALARM                                                                                                                                              |                                                                                    |                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |            |                           |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------|
| MODEL NUMBER                                                                                                                                                       |                                                                                    | TYPE                                | FEATURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | PRICE      | DATA SHEET                |
| HF-S2E                                                                                                                                                             |   | Standalone Smoke Detector           | Photoelectric smoke alarm can sense and detect the smoke, fire, etc., and send out sounder strobe alarm signals, which is widely used in shops, residences, hotels, rentals and other independent scenes.                                                                                                                                                                                                                                                                                              | ₹ 710.00   | <a href="#">Datasheet</a> |
| HF-S2                                                                                                                                                              |                                                                                    |                                     | Alarm indicating buzzer, sound level ≥ 85dB@3 m<br>Battery life: 3 years (AA × 2), easy to replace<br>Supports multiple alarm types: low battery alarm, maze dirty alarm<br>Supports self-check function to verify whether the device is working properly<br>Supports silence and reset locally<br><b>Support IO alarm in Model HF-S2</b>                                                                                                                                                              | ₹ 850.00   | <a href="#">Datasheet</a> |
| NP-FY200                                                                                                                                                           |   | Standalone Smoke & Heat Detector    | Dual-light sensing technology for reducing false alarm caused by vapor.<br>Alarm indicating buzzer, sound level ≥ 85 dB @ 3 m (A-Weighted).<br>Powered by lithium battery, long battery life under normal operation.<br>Supports test feature to verify whether the device is working properly.<br>Supports multiple alarm types: low voltage alarm, tampering alarm, maze dirty alarm.<br>Constant temperature alarm/Differential temperature alarm.<br>Supports remote control to silence the alarm. | ₹ 2,210.00 | <a href="#">Datasheet</a> |
| HF-GM100                                                                                                                                                           |   | Standalone Carbon Monoxide Detector | Advanced electrochemical CO sensor technology<br>Digital temperature compensation technology<br>Low battery warning<br>Anti-RF interference<br>LCD back light, visible in the dark (Optional)<br>Hush mode: silence an unwanted Detector                                                                                                                                                                                                                                                               | ₹ 2,210.00 | <a href="#">Datasheet</a> |
| HF-GP110                                                                                                                                                           |  | Standalone GAS Detector             | <b>The Standalone Liquefied Petroleum Gas Alarm provides the users an early alert, when the natural gas leakage in the protected area reaches the alarm concentration</b>                                                                                                                                                                                                                                                                                                                              | ₹ 1,720.00 | <a href="#">Datasheet</a> |
| HF-GN110                                                                                                                                                           |                                                                                    |                                     | Support multiple function, alarm, test, silence, fault and malfunction.<br>Support log saving function, record alarm, alarm recovery, fault, fault recovery, sensor failure and other types of logs.<br>Support valve output and fan output<br><br><b>LGP Detector : HF-GP110</b><br><b>PNG Detector : HF-GN110</b>                                                                                                                                                                                    | ₹ 1,720.00 | <a href="#">Datasheet</a> |
| Authorized Distributor -<br><br>Servius Infotech Pvt. Ltd.<br>CIN : U72200MP2015PTC034176<br>Website : <a href="https://www.servius.in">https://www.servius.in</a> |                                                                                    |                                     | Bhopal Branch<br>Plot No 44, Zone-1, MP Nagar, Bhopal 462011, Madhya Pradesh<br>Email : <a href="mailto:parmar@servius.in">parmar@servius.in</a><br>Phone : 0755 - 4203580   Mobile : 9329929100<br><br>Indore Branch<br>LG - 1 & 2, Silver Sachora Castle<br>RNT Marg, Indore, Madhya Pradesh<br>Email : <a href="mailto:setu.dangi@servius.in">setu.dangi@servius.in</a><br>Phone : 0731 - 4963851   Mobile : 9329929101                                                                             |            |                           |

| CAR DASH CAMERA |                                                                                     |            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |            |                           |
|-----------------|-------------------------------------------------------------------------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------|
| MODEL NUMBER    | IMAGE                                                                               | Model      | FEATURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | PRICE      | DATA SHEET                |
| AE-DC2018-K2    |    | K2         | <ul style="list-style-type: none"> <li>Up to 1080P HD camera with horizontal 102° wide angle, diagonal 122°.</li> <li>Support built-in MIC and speaker for audio in and out.</li> <li>Communication: Built-in Wi-Fi module.</li> <li>Supports TF card storage (Max.128GB) and recording overwrite.</li> <li>Phone App: live view, record playback and parameter configuration.</li> <li>Built-in G-Sensor module, support video recording linkage at car crash or strong vibration. (Linkage video record can be configured be no-overwritten)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                             | ₹ 1,899.00 | <a href="#">Datasheet</a> |
| AE-DC4018-D1PRO |    | D1         | <p>Up to 1440P high resolution, with horizontal 102.6° wide angle, diagonal 121.8°.</p> <p>Support built-in MIC and speaker for audio in and out.</p> <p>Built-in WIFI module and WIFI AP function supported.</p> <p>TF card for video recording, up to 256GB. (Overwriting supported)</p> <p>Built-in G-Sensor module, support video recording linkage at car crash or strong vibration. (Linkage video record can be configured be no-overwritten)</p> <p>Phone App: live view, record playback and parameter configuration.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | ₹ 2,599.00 | <a href="#">Datasheet</a> |
| AE-DC5013-F6PRO |    | F6 PRO     | <ul style="list-style-type: none"> <li>High Resolution Up to True 1600p (2560 x 1600)</li> <li>Wide Field of View, 130° Diagonal, 109° Horizontal</li> <li>f/1.6 Large Aperture for Crisp Night Imaging</li> <li>Microphone and Speaker</li> <li>Wi-Fi AP Module</li> <li>GPS</li> <li>G-Sensor Module</li> <li>MicroSD Card Up to 128 GB Supported</li> <li>Phone App for Setup, Live View, Recording, Search, Backup, etc.</li> <li>Voice Control and ADAS (Advanced Driver Assistant System) Supported</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | ₹ 5,950.00 | <a href="#">Datasheet</a> |
| AE-DC2328-C200S |   | C200S(2ch) | <p>Up to 1080P high resolution, with horizontal 107° wide angle, diagonal 128°.</p> <p>F2.0 super large aperture offer a perfect night image.</p> <p>Support built-in MIC and speaker for audio in and out.</p> <p>Display: 3 inches IPS screen, Resolution: 360*640.</p> <p>Built-in WIFI module and WIFI AP function supported.</p> <p>Built-in G-Sensor module, support video recording linkage at car crash or strong vibration. (Linkage video record can be configured be no-overwritten)</p> <p>TF card for video recording, up to 256GB. (Overwriting supported)</p> <p>Phone App: live view, record playback and parameter configuration.</p> <p>Easy installation and user friendly, plug and play. (Automatically recording after power on)</p> <p>Low power consumption and high performance.</p>                                                                                                                                                                                                         | ₹ 4,200.00 | <a href="#">Datasheet</a> |
| AE-DC8012-C8    |  | C8 (2Ch.)  | <p>Up to 2160P high resolution, with horizontal 118° wide angle, diagonal 143°.</p> <p>F1.75 super large aperture offer a perfect night image.</p> <p>Support built-in MIC and speaker for audio in and out.</p> <p>Built-in WIFI module and WIFI AP function supported.</p> <p>Built-in G-Sensor module, support video recording linkage at car crash or strong vibration. (Linkage video record can be configured be no-overwritten )</p> <p>Support GPS module with speed display and route tracking playback.</p> <p>TF card for video recording, 32GB to 256GB (Overwriting supported)</p> <p>Phone App: live view, record playback and parameter configuration.</p> <p>Voice recognition supported : Snapshot, Recording on, Recording off.</p> <p>ADAS supported: "Traffic light turn green", "Speed limit recognition", "Front car start remind".</p> <p>Easy installation and user friendly, plug and play. (Automatically recording after power on )</p> <p>Low power consumption and high performance.</p> | ₹ 8,300.00 | <a href="#">Datasheet</a> |

Authorized Distributor -

**Servius Infotech Pvt. Ltd.**  
 CIN : U72200MP2015PTC034176  
 Website : <https://www.servius.in>

**Bhopal Branch**  
 Plot No 44, Zone-1, MP Nagar, Bhopal 462011, Madhya Pradesh  
 Email : [parmar@servius.in](mailto:parmar@servius.in)  
 Phone : 0755 - 4203580 | Mobile : 9329929100

**Indore Branch**  
 LG - 1 & 2, Silver Sachora Castle  
 RNT Marg, Indore, Madhya Pradesh  
 Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)  
 Phone : 0731 - 4963851 | Mobile : 9329929101

| Audio System      |                                                                                     |                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |             |                           |
|-------------------|-------------------------------------------------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|---------------------------|
| MODEL NUMBER      | IMAGE                                                                               | Model                                         | FEATURE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | PRICE       | DATA SHEET                |
| DS-QAE0A60G1-VB   |    | Analog Amplifier <b>60W</b><br><b>2 Zone</b>  | Support four types of audio input: Bluetooth, USB flash drive, microphone, and RCA, with flexible and convenient operation<br>Built-in Bluetooth module, support fast Bluetooth playback<br>Support plugging in the USB flash drive to play audio sources<br>Support independent microphone volume control and two-channel partition volume control<br>Support two-channel audio mixing output<br>Adopt high-strength engineering plastics, sturdy and durable<br>Integrated functional design, convenient and reliable | ₹ 5,320.00  | <a href="#">Datasheet</a> |
| DS-QAE0A120G1-VB6 |    | Analog Amplifier <b>120W</b><br><b>2 Zone</b> | 120W Analog Amplifier<br>6 Zone<br>2-AUR in<br>2 Mic in                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | ₹ 14,800.00 | <a href="#">Datasheet</a> |
| DS-QAE0A240G1-VB6 |                                                                                     | Analog Amplifier <b>240W</b><br><b>2 Zone</b> | 1-EMC in<br>1-RCA Out                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | ₹ 18,700.00 | <a href="#">Datasheet</a> |
| DS-QAE0MG0G1      |    | Gooseneck Paging Microphone                   | High SNR sound inlet basket with balanced frequency response. Features a high-sensitivity, low-noise preamp for clear long-distance speech capture and quality audio transmission. The flexible gooseneck allows easy angle adjustment, while the integrated design prevents shaking and poor contact. A droplet-shaped pickup reduces sound field interference. Supports 12V DC and 48V phantom power with voltage adaptive technology.                                                                                | ₹ 4,150.00  | <a href="#">Datasheet</a> |
| DS-QAE0203G1-V    |    | Analog Ceiling Speaker <b>3W</b>              | Adopting a composite paper fiber sound basin, the sound quality is clear and bright                                                                                                                                                                                                                                                                                                                                                                                                                                     | ₹ 530.00    | <a href="#">Datasheet</a> |
| DS-QAE0206G1-V    |                                                                                     | Analog Ceiling Speaker <b>6W</b>              | With the design of powerful steel spring clamp, the installation is fast and safe<br>Support ceiling mounting installation with a simple appearance                                                                                                                                                                                                                                                                                                                                                                     | ₹ 580.00    | <a href="#">Datasheet</a> |
| DS-QAE0330G1T-V   |  | Analog Horn Speaker <b>30W</b>                | High sensitivity and high sound, long transmission distance<br>Multiple power levels are optional<br>IP65                                                                                                                                                                                                                                                                                                                                                                                                               | ₹ 1,680.00  | <a href="#">Datasheet</a> |
| DS-QAE0120G1R     |  | Analog Cabinet Speaker <b>20W</b>             | By using U-brackets, the installation surface angle can be adjusted for convenient installation<br>Support horizontal and vertical installation<br><b>Available in two Color (Black, White)</b>                                                                                                                                                                                                                                                                                                                         | ₹ 3,120.00  | <a href="#">Datasheet</a> |
| DS-QAE0420G1-V    |  | Analog Column Speaker <b>20W</b>              | The speaker unit adopts aerospace magnetic, imported adhesive coating, and lightweight sound film design, with high sensitivity, bright sound, and long transmission distance<br>Adopt professional engineering reinforced plastics with high strength<br>By using L-brackets, the installation surface angle can be adjusted for convenient installation<br>Professional integrated design, supporting IP66 waterproof, with a simple and beautiful appearance                                                         | ₹ 3,500.00  | <a href="#">Datasheet</a> |

Authorized Distributor -

**Servius Infotech Pvt. Ltd.**CIN : U72200MP2015PTC034176  
Website : <https://www.servius.in>**Bhopal Branch**Plot No 44, Zone-1, MP Nagar, Bhopal 462011, Madhya Pradesh  
Email : [parmar@servius.in](mailto:parmar@servius.in)  
Phone : 0755 - 4203580 | Mobile : 9329929100**Indore Branch**LG - 1 & 2, Silver Sachora Castle  
RNT Marg, Indore, Madhya Pradesh  
Email : [setu.dangi@servius.in](mailto:setu.dangi@servius.in)  
Phone : 0731 - 4963851 | Mobile : 9329929101