

## DS-1LH1SCAM593C Coaxial Cable with power cable



### Features and Functions

- 180m mini RG59 coaxial cable with power cable
- Conductor material of Coaxial cable is Bare copper
- Braiding material of Coaxial cable is Copper clad aluminum magnesium
- Conductor material of power cable is Bare copper
- Excellent anti-interference performance
- Excellent anti-aging performance



## Specifications

| Model                |                          | DS-1LH1SCAM593C                |
|----------------------|--------------------------|--------------------------------|
| <b>Coaxial Cable</b> |                          |                                |
| <b>Conductor</b>     | <b>Material</b>          | Bare copper                    |
|                      | <b>Wire Gauge</b>        | 26AWG                          |
|                      | <b>Diameter</b>          | 0.41 ± 0.01mm                  |
| <b>Insulation</b>    | <b>Material</b>          | FPE                            |
|                      | <b>Diameter</b>          | 2.0 ± 0.1mm                    |
| <b>Tape</b>          | <b>Material</b>          | Copper foil                    |
| <b>Braid</b>         | <b>Material</b>          | Copper clad aluminum magnesium |
|                      | <b>Braiding Standard</b> | 5*16*0.12mm ± 0.008mm          |
|                      | <b>Braiding Density</b>  | ≥80%                           |
| <b>Jacket</b>        | <b>Material</b>          | PVC                            |
| <b>Impedance</b>     |                          | 75ohms                         |
| <b>Power Cable</b>   |                          |                                |
| <b>Conductor</b>     | <b>Material</b>          | Bare copper                    |
|                      | <b>Quantity</b>          | 3                              |
|                      | <b>Diameter</b>          | 11*0.16 ± 0.008mm              |
| <b>Insulation</b>    | <b>Material</b>          | SR-PVC                         |
|                      | <b>Diameter</b>          | 1.2 ± 0.1mm                    |
| <b>Jacket</b>        | <b>Material</b>          | PVC                            |
| <b>General</b>       |                          |                                |
| <b>Length</b>        |                          | 180m                           |
| <b>Color</b>         |                          | Black                          |

Distributed by

## Available Model

**DS-1LH1SCAM593C**

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
saleseuro@hikvision.com

**Hikvision Middle East**  
T +971-4-8816086  
salesme@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-444  
info.fr@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
poland@hikvision.com

**Hikvision UK**  
T +44-1628-9021-4  
support.uk@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Oceania**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision Hong Kong**  
T +852-2151-1761

**Hikvision Canada**  
T +1-909-895-0400  
sales.usa@hikvision.com