

CP-UNR-4K2162-V3

16CH 1U 2HDDs Network Video Recorder

- Up to 16 Channel IP Camera input
- Instastream, H.265, H.264, MJPEG
- Up to 12 MP resolution preview and playback
- AI disabled: 144 Mbps incoming, AI enabled: 72 Mbps incoming
- Support 2 SATA HDDs up to 20TB, 2 USB ports(2.0)
- HDMI / VGA simultaneous video output
- ONVIF Version 21.12 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro Lite



System Overview

This NVR has gathered momentum across the globe for its outstanding performance and premium recording quality as it can be applied in any situation for IP video surveillance. This Series of NVRs supports the input, recording and transmission functions. Along with that, this NVR also enjoys the help of a built-in deep learning module as this product adopts the video image that is structured on deep learning algorithms. This NVR lets you achieve high-precision human face-recognition and efficient perimeter protection.

This product has been crafted to pay attention to what matters the most through applying deep learning artificial intelligence, which makes it fasten the event response time and helps in making the video more actionable.



CP-UNR-4K2162-V3

16CH 1U 2HDDs Network Video Recorder

Functions

Face Recognition

This technology can be used to extract faces from a range of cameras and is capable of processing large quantities of faces in real-time or post-event and can provide alerts to help with access and authentication, border security, and crowd control.

Smart Motion Detection (SMD Plus)

CPPLUS has introduced Smart Motion Detection, AI-based SMD, which use an advanced algorithm to differentiate human and vehicular shapes within a scene and send alarms only when a person or vehicle is detected.

Instastream

This camera has been designed with the latest and most efficient innovation among the standard video compression designs. Smart encoding algorithms developed by CP PLUS help in saving up to 70% more bandwidth than H.265 along with making it more beneficial for minimizing bandwidth and storage costs. It enhances video coding efficiency while providing high resolution and the rate of frame in the video using Intelligent Region Perception to detect motion in each frame.

Face Detection

With the help of the deep learning algorithm that is used in this technology, people can easily be detected, tracked, recorded, and captured. It takes only a second to detect one human face. Face detection is useful in cameras to help with auto-focus. This technology is mainly used to identify the presence of a human face.

gCMOB/ iCMOB

Designed to allow users to access and control live streaming from CP PLUS IP Cameras, DVRs/ NVRs and Video Door Phones, the CP PLUS gCMOB/ iCMOB application offers a host of features such as Easy GUI, up to 16 live viewing split-ups; InstaOn cloud support; Playback; digital zoom ins; two-way talk, and more.

KVMS Pro Lite

The KVMS Pro Lite is a hybrid security management software that allows the management of various surveillance devices such as cameras, DVRs/ NVRs, encoders/ decoders, etc. It is released with the surveillance hardware and exclusively supports CP PLUS devices.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-UNR-4K2162-V3

16CH 1U 2HDDs Network Video Recorder

Feature	Specification
Processor	Industrial-grade processor
Operating System	Embedded LINUX
IP Camera Input	16 channel
User Interface	Web, Local GUI
Video Output	1 HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 1 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
Video Compression	H.265, H.264, MJPEG
Encode Strategy	Instastream
Decoding Capability	AI disabled: 1-channel 12 MP@30 fps, 1-channel 8 MP@30 fps, 2-channel 5 MP@30 fps, 3-channel 4 MP@30 fps, 6-channel 1080p@30 fps AI enabled: 1-channel 8 MP@30 fps, 1-channel 5 MP@30 fps, 2-channel 4 MP@30 fps, 4-channel 1080p@30 fps
Video Resolution	12 MP, 8 MP, 6 MP, 5 MP, 4 MP, 3 MP, 2MP, 960p, 1MP, D1
Video Display Split	Main screen: 1/4/8/9/16/25/36 Sub screen: 1/4/8/9/16
SMD Plus by NVR	4 channels
SMD Plus by Camera	Perimeter protection, SMD Plus
Network Bandwidth	AI disabled: 144 Mbps incoming, 144 Mbps recording and 72 Mbps outgoing AI enabled: 72 Mbps incoming, 72 Mbps recording and 36 Mbps outgoing
Smart Phone	iPhone, iPad, Android Phone
Interface Ports	2 (1 front USB 2.0 port, 1 rear USB 2.0 port)
Protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, SNMP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, PPPoE, FTP, DDNS, Alarm Server, IP Search, Multicast, InstaOn cloud, Auto Registration, ONVIF 2.1.12(Profile T, Profile S, Profile G)
Ethernet	1 (10/100/1000 Mbps Ethernet port, RJ-45)
Browser	Chrome, IE9 and later, Firefox, Edge

Feature	Specification
Abnormality Alarm	No disk, disk error, low space, low quota space, network disconnection, IP conflict, MAC conflict, video loss, video tampering, camera offline
Intelligent Alarm	Perimeter protection, SMD Plus
General Alarm	Motion detection, camera external alarm, PIR alarm
Alarm Linkage	Recording, snapshot, buzzer, log, preset, email, tour
Alarm Input	NA (4 channels are optional)
Alarm Output	NA (2 channels are optional, one of them is 1-channel 12 V 1 A output)
Audio Input	1-channel RCA
Audio Output	1-channel RCA
Audio Compression	G.711a, G.711u, PCM, G726, AAC
Hard Disk	2 SATA ports. Each disk can contain up to 20 TB. this limit varies depending on the environment temperature
Multi-Channel Playback	Up to 16 channels
Record Mode	General, motion detection, intelligent, alarm
Playback Mode	Instant playback, general playback, event playback, tag playback, smart playback (face and motion detection)
Backup Method	USB device and network
Power Supply	12 VDC, 4 A
Power Consumption	≤ 10 W (without HDD)
Operating Temperature	-10 °C to +55 °C (14 °F to +131 °F)
Operating Humidity	10%–93% (RH)
Storage Temperature	-20 °C to +60 °C (–4 °F to +140 °F)
Dimensions	375.0mm × 282.9mm × 53.0mm
Weight	1490 g (without HDD)

Dimensions (mm/inch)

Accessories : Optional

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com