

PT-HTD11F0E-WPF(M)

2MP Fixed Bullet Ranginview Camera with Audio



Ranginview



Key Features

- 2MP resolution delivers high quality images
- 3D DNR technology delivers clean and sharp images
- Up to 20 m white light & IR distance for bright night imaging
- Built-in mic captures high quality audio over coaxial cable,
- One port for four switchable signals (TVI/AHD/CVI/CVBS)
- Water and dust resistant (IP66)

Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution (H x V)	1920 × 1080
Min. Illumination	0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	ICR
Angle Adjustment	Pan: 0 to 360°, tilt: 0 to 180°, rotate: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	Fixed focal lens, 2.8 mm and 3.6 mm optional
Focal Length & FOV	2.8 mm, horizontal FOV: 100°, vertical FOV: 55°, diagonal FOV: 116° 3.6 mm, horizontal FOV: 80°, vertical FOV: 43°, diagonal FOV: 95°
Lens Mount	M12
Illuminator	
Supplement Light Type	White Light, IR
Supplement Light Range	Up to 20 m
Image	
Image Settings	Brightness, Sharpness, Smart IR
Frame Rate	TVI: 1080P @30 fps, 1080P @25 fps AHD: 1080P @30 fps, 1080P@25 fps CVI: 1080P @30 fps, 1080P @25 fps CVBS: PAL/NTSC
Day/Night Mode	Auto/Colour/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
Built-in Microphone	Yes
General	
Material	Plastic
Dimension	161.22 × 57.97 × 61.96 mm (6.35 × 2.28 × 2.44 inch)
Weight	Approx. 164 g
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F). Humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25% * It is recommended to use one power adapter to supply power for one camera.
Consumption	Max. 3.2 W
Protection	IP66

*Specifications are subject to change without prior notice. *Product picture may differ as per actual.

Available Model
PT-HTD11F0E-WPF(M)

Dimension

